

# TS9 WET TILE SAW

A 230 mm professional grade, high precision wet tile saw with unique water recirculation design. 48 mm depth of cut. 45° bevel cut capability.



Quick-release table mountings.



Easy mounting 1.5 L water tray



Angle Guide Plate & Micro-adjustable cutting guide

Model	TS9
Motor Type	Single Phase AC Induction
Power Output	800 W
Voltage, Frequency	220-240 V~ 50-60 Hz or 110-120 V~ 50-60 Hz
No Load Speed	3000 min <sup>-1</sup> (50 Hz), 3600 min <sup>-1</sup> (60 Hz)
Max. Blade Diameter	230 mm (9")
Blade Bore	25.4 mm (1")
Bevel Capability	0-45°
Max. Cutting Depth-straight	48 mm (1-7/8")
Max. Cutting Depth- at 45°	37 mm (1-7/16")
Rip Cut - Left	305 mm (12")
Rip Cut - Left at 45° Bevel	295 mm (11-39/64")
Rip Cut - Right	147 mm (5-25/32")
Diagonal (Miter) Cut - Left	285 mm (11-7/32")
Diagonal Cut - Left at 45° Bevel	275 mm (10-13/16")
Front of Blade to Table Edge	200 mm (7-7/8")
Ingress Protection	IP44
Dimensions (LxWxH)	660 x 595 x 320 mm
Weight	14.7 kg (32.4 lb)
Characteristics / Certification	<b>CE CB</b>

## Features

1. Easy Miter adjustment miters up to 45 degrees.
2. Easy mounting 1.5 L water tray.
3. Quick-release table mountings. Quick tool-free removal of the table for easy cleaning and blade replacement.
4. Rugged, stable, and easy-to-clean table with cutting scale.
5. Micro-adjustable cutting guide always remains parallel.
6. Angle Guide Plate holds work pieces at various angles.

### Standard Accessories

- Diamond Blade
- Parallel Cutting Guide
- Angle Guide Plate
- M8 Combination Wrench
- M19 Combination Wrench